
GRABO PRO-LIFTER 20 HEAVY LIFTING MADE EASY



Specifications:

GRABO PRO-LIFTER 20 / GP-1Li-FB
14.8VDC 2600mAh Li-ion
16W
100-240VAC 50/60Hz
~2hrs
1.5hrs
900 ON-OFF cycles of 10 seconds
30 days
100000+ ON-OFF cycles / 800+ hrs continuous
0.7cfm (20 L/min)
11.6Psi (0.8 Bar, 80 kPa)
375Lbs (170 kg)
11.77 x 7.22 x 4.76" (300 x 184 x 121 mm)
3.2Lbs (1.5 kg)
32°F~140°F (0°~60 °C)
Peak/valley heights less than 0.1" (3mm), arc less than 5°
Pump stops automatically at maximum vacuum rate (11.6Psi / 0.8 Bar)

Lifting Capacity:

Material Direction	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry Wall
Perpendicular	375Lbs	375Lbs	242Lbs	220Lbs	220Lbs	176Lbs	176Lbs	165Lbs
Hold	(170 kg)	(170 kg)	(110 kg)	(100 kg)	(100 kg)	(80 kg)	(80 kg)	(75 kg)
Parallel Hold	265Lbs	265Lbs	242Lbs	220Lbs	143Lbs	176Lbs	176Lbs	143Lbs
	(120 kg)	(120 kg)	(110 kg)	(100 kg)	(65 kg)	(80 kg)	(80 kg)	(65 kg)

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.

NOTICE: Due to the high pressure that is created with the GRABO® Pro-Lifter 20 we strongly recommend that you do not attempt to attach the GRABO® Pro-Lifter 20 to glass thinner than 6mm thick. Damage can occur to glass that is thinner than 6mm thick.

By Nemo Power Tools www.GRABO.com

GRABO headquarters:

Eastern Commerce Center 6000 S Eastern Ave Unit 9E Las Vegas, Nevada, 89119

Info@GRABO.com

www.GRABO.com

Main Office: +1 (844) 430-0510

Help & Warranty: +1 (702) 718-2433