

# **NEMO GRABO - HEAVY LIFTING MADE EASY**





## **Specifications:**

Model/SKU	NEMO GRABO / NG-2B-FB			
Battery	14.8VDC 2600mAh Li-ion			
Rated Power	16W			
Charger Input Voltage	100-240VAC 50/60Hz			
Battery Charging Time	~2hrs			
Non-Stop Running Time (Full Charge)	1.5hrs			
Running Cycles (On Full Charge)	900 ON-OFF cycles of 10 seconds			
Stand-by Mode (Charge Hold)	30 days			
Pump Service Life	100000+ ON-OFF cycles / 800+ hrs continuous			
Rated Air Flow	0.7cfm ( 20 L/min )			
Maximum Vacuum Rate	11.6Psi ( 0.8 Bar, 80 kPa )			
Maximum Lifting Capacity	375Lbs ( 170 kg )			
LxWxH	11.67 x 7.12 x 4.76" ( 297 x 181 x 121 mm )			
Net Weight (With Battery)	3.3Lbs ( 1.6 kg )			
Working Temperature	32°F~140°F (0°~60 °C)			
Applicable Surface Type	Peak/valley heights less than 0.1" ( 3mm ), arc less than 5°			

## Lifting Capacity:

Material Direction	Glass	Ceramic Tiles	Metal	Plastic	Wood	Rough Slate	Rough Concrete	Dry Wall
Perpendicular	375Lbs	375Lbs	242Lbs	220Lbs	220Lbs	176Lbs	176Lbs	165Lbs
Hold	( 170 kg )	( 170 kg )	( 110 kg )	( 100 kg )	( 100 kg )	( 80 kg )	(80 kg)	(75 kg)
Parallel Hold	265Lbs	265Lbs	242Lbs	220Lbs	143Lbs	176Lbs	176Lbs	143Lbs
	( 120 kg )	(120 kg)	(110 kg)	(100 kg)	(65 kg)	( 80 kg )	( 80 kg )	(65 kg)

Based on product information at time of publication. Environmental conditions can affect product performance and longevity; consult the product manual on GRABO.com or contact a Sales Representative for more information.

NOTICE: Due to the high pressure that is created with the Nemo GRABO® we strongly recommend that you do not attempt to attach the Nemo GRABO® to glass thinner than 6mm thick. Damage can occur to glass that is thinner than 6mm thick.

### By Nemo Power Tools - www.GRABO.com

#### **GRABO** headquarters:

Eastern Commerce Center 6000 S Eastern Ave Unit 9E Las Vegas, Nevada, 89119

Info@GRABO.com

www.GRABO.com

**Main Office:** +1 (844) 430-0510

Help & Warranty: +1 (702) 718-2433